

XL pull-out unit for 2,700 mm beams

400 kgs load capacity| 70 % pull-out

XL pull-out units can be integrated into existing pallet racks. They are placed on the cross beams and bolted in the rear area. Loading can be done from the forklift corridor as well as from the picking corridor. The unit runs on ball bearings. The pull-out unit is delivered unassembled. A fastening set is included in the scope of delivery.

Product details

Load capacity	400 kgs (evenly loaded)
Pull-out depth	70 %
Material	Steel
Empty weight	50 kgs
Suitable for rack depth	970 - 1,170 mm
Configuration	3 handles

Commodity code	73089098
Packaging unit	1 piece
Max. Quantity / pallet	4 pieces

Version

Dimension (WxDxH)	Colour	Art-No.
2,600 x 1,251 x 51 mm	RAL 5010	44702600
2,600 x 1,251 x 51 mm	RAL 7024	44702600






Please specify a colour when ordering.



Fully extended pull-out unit




Closed pull-out unit

LOAD	PULL-OUT	COLOUR	COLOUR	MAX. QUANTITY/ PALLET
				
400	70	5010	7024	4

XXL pull-out unit for 2,700 mm beams

400 kgs load capacity| 70 % pull-out

Engineering drawing



Dimension

Number	Size (in mm)
A 1	2,600 mm
A 2	71 mm
B 1	1,251 mm
B 2	51 mm
C 1	1,208 mm
C 2	2,600 mm
C 3	1,251 mm
D 1	830 mm

Mounting kit

Screws	Beams
M8 x 140	For beam height up to 115 mm
Screws for other beam heights on request!	

XL pull-out unit for 2,700 mm beams

400 kgs load capacity| 70 % pull-out

Important safety instructions

- The pallet rack must be securely anchored to the floor. Please follow the assembly and safety instructions of the rack manufacturer
- Beams must be firmly bolted to the support uprights (using at least M8 bolts)
- Pull-out units must be fixed using the bolts, nuts, washers and counterplates supplied according to the assembly instructions
- Depending on the different pull-out units and the length of the beams, the rack must have a minimum shelf load according to the table below
- The maximum load capacity of the pull-out units with an evenly distributed load and safety instructions are attached to the pull-out units
- If there are several pull-out units on one beam, only one unit is allowed to be pulled-out at a time
- If there are several levels with pull-out units, only one unit may be extended at a time
- Immediately after using the pull-out unit, it must be pushed back again and it must be ensured that it is locked in place

Necessary shelf load of the beams

L = 2,700 mm 1 pull-out unit
1,057 kgs

Data sheet, status 03.2025
Errors and omissions excepted. All values are approximate. Pictures may show accessories or other products.